



Disclaimer

Any information contained in this Brochure is provided for informational purpose only and is subject to change without notice.

For Technical Data on any of our Products please visit us at **www.blackrockmining.net**

Our Range



CENTRIFUGAL



AIR DIAPHRAGM



LOBE



UL FM FIRE PUMP



SUBMERSIBLE



PRESSURE SYSTEMS



GEAR




SLURRY



DRUM PUMP



OIL SEPERATORS



Screw Pumps



Self Priming



PULSATION DAMPNERS



INJECTORS



Multistage



Magnetic Drive

Disclaimer

Any information contained in this Brochure is provided for informational purpose only and is subject to change without notice.

For Technical Data on any of our Products please visit us at www.blackrockmining.net



Pumping



Tracability



Lubrication


Blackrock Mining are the Mackay Distributor for Allpumps and we offer full Sales and Service On your Pumping and Lubrication needs.



Flexi Stoppings



Ventilation



RocLiner

Strata Linings Flexible Stoppings are over-pressure rated and certified as FRAS (Fire-Resistant and Anti-Static) as per MDG 3608. The stoppings can be supplied in standard kit form or customised for any job for segregation, 2 PSI, 5 PSI & now 20 PSI ratings.

layflat ventilation ducting is manufactured using a high strength PVC Fabric, which makes it ideal for use in underground auxiliary ventilation applications in both mining and tunnelling applications. Sizes from 600-2400mm in various lengths.

RocLiner is a premium sprayable membrane. RocLiner comprises a superior blend of Portland cementitious binder, graded sand, and a co-polymer of vinyl acetate and ethylene with mineral additives and a protective colloid.



Hire Fleet

Enquire about our Range of Hire Equipment. Spray Pumps, Air Tracks, Grout Pumps, Cement Dispenser etc



Dustless

The Ventsec Wet applicator Pumping System is a Phase forward in the prevention of Dust Disease in the underground mining industry and Civil.



Vshot

Dustless Spray and Pumping application. Various types on application.

Disclaimer

Any information contained in this Brochure is provided for informational purpose only and is subject to change without notice.

For Technical Data on any of our Products please visit us at www.blackrockmining.net

Dustless Spraying .



Sole Queensland Distributor.

PERFORMANCE SPECIFICATIONS

Pumping rate	18-25LPM
Spray application rate	17-20LPM
Maximum air supply pressure	750kPa
Maximum air supply flow rate	151LPS
Maximum water supply pressure	1770kPa

OPERATING LIMITS AND CAPABILITIES

Gross weight	1200kg
Length	2000mm
Width	1300mm
Height	1800mm
Pneumatic powered	60-100psi
Pumping output (distance)	10-25m



PRODUCT SPECIFICATIONS

PRODUCT	APPLICATION
Vshot-S	Wet Application Standard Shotcrete ranging from 24-80MPA (Engineered) for all general shotcrete applications.
Vshot-FS	Wet Application Fast Set Shotcrete ranging from 50-80MPA with set times at 15min, 25MPA in 12hrs. Commonly utilised in water control activities.
Vshot-HS	Wet Application High Strength Shotcrete ranging from 80-120MPA utilised in Industrial and heavy civil industries.



Sprayed Application

Disclaimer

Any information contained in this Brochure is provided for informational purpose only and is subject to change without notice.

For Technical Data on any of our Products please visit us at www.blackrockmining.net